

Provisional Specifications - Europe



3 cabins 2 heads version:



3 cabins 3 heads - Skipper's cabin version:





GENERAL SPECIFICATIONS * _____

 L.O.A Hull length L.W.L. Beam Standard draft (T-keel) Standard ballast weight (Cast iron) Shallow draft Shallow draught keel Weight of shallow draft keel (Cast iron) Air draft (excluding antennae) 	17,12m 15,98m 15,40m 5,00m 2,50m 4 500kg 1,95m 2,00m 5 130kg 24,00m	56'2" 52'5" 50'6" 16'5" 8'2" 9,918 lbs 6'5" 6'7" 11,307 lbs 78'9"
 Performance air draught (excluding antennae) Light displacement Fuel capacity (standard) Fresh water capacity (standard) Engine power: Sail drive (standard) Sail drive Dock&Go (Option) Propeller shaft (Option) 	25,80m 16 600kg 400L 720L 80 HP 80 HP 110 HP	85' 36,586 lbs 106 US Gal 190 US Gal 80 HP 80 HP 110 HP

ARCHITECTS / DESIGNERS _

- Naval Architect: BISCONTINI YACHT DESIGN
- Outside & interior design: LORENZO ARGENTO

EC CERTIFICATION * _____

- Category A 10 people
 Category B 12 people
 Category C 14 people

STANDARD SAILS DIMENSIONS * ___ **ALUMINIUM MAST WITH IN-BUILT FURLER**

Furling mainsail	63,00m ²	678 sq/ft
Self-tacking jib	51,00m ²	549 sq/ft
 Furling genoa (105 %) 	65,00m ²	700 sq/ft
• Code 0	123,00m ²	1,324 sq/ft
 Asymmetric spinnaker 	210,00m ²	2,260 sq/ft
• 1	19,90m	<i>65[']3''</i>
• J	6,80m	22'4"
• P	20,00m	65'7''
• E	6,80m	22'4"

PERFORMANCE CLASSICAL ALUMINIUM MAST (+ 1,80m /

 Performance version mainsail 	83,00m ²	894 sq/ft
 Self-tacking jib 	56,00m ²	603 sq/ft
 Furling genoa (105 %) 	70,00m²	754 sq/ft
• Code 0	135,00m ²	1,453 sq/ft
 Asymmetric spinnaker 	260,00m ²	2,800 sq/ft
•1	21,75m	75'2"
• J	6,80m	22'4''
• P	22,00m	<i>75'6''</i>
• E	6,80m	22'4''

^{*} Provisional specifications, boat in process of certification.



Provisional Specifications - Europe

STANDARD EQUIPMENT

CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- ISO 12215 certified structure
- Balsa sandwich infusion hull
- Vacuum infused structural inner liner (Fabrics resin) bonded to the hull
- Deck in glass fibre/balsa wood sandwich infusion, with non-slip "diamond point" surface
- Cast iron keel attached with bolts and bonded stainless steel backplate
- Twin rudders hung with stainless steel stock
- White coloured hull Aluminium grey hull decoration
- · 8 Hull portholes

DECK EQUIPMENT

RIGGING

- · Depending on version:
- Aluminimum mast with in-mast furling deck-stepped, 2 Aft swept spreaders
- **Performance classical aluminimum mast** deck-stepped (+ 1,80m / 5'11') 3 Aft swept spreaders
- Split backstay (Hydraulic optional extra)
- · Single-strand rigging
- Anodised aluminium boom
- · Harken blocks at mast foot
- · Rigid boom vang with tackle
- 2 Štand-up blocks for mainsail sheet on mainsail cradle
- 1 Self-tacking jib track with traveller
- All lines brought back to the helm stations (except boom uphaul and Genoa halyard)
- · Complete running rigging:
 - Mainsail halyard
 - Genoa halyard with on-mast tensioner
 - Boom topping lift with cleat on mast
 - Mainsheet
 - 1 Self-tacking jib sheet
- · Mainsail furtler and self-clinching jib furler on deck
- 7 Halyard clutches (1 triple to starboard, 2 doubles to port)
- · Halyard covers
- 1 Flag halyard

WINCHES

- 1 Manual self-tailing winch to starboard (H50.2 STA)
- 1 Port side manual self-tailing winch (H50.2 STA)
- 1 Aluminium Speed Grip winch handle
- · Stowage of which handles in dedicated space in rope bags

SAILS (INCIDENCES)

- Dacron furling mainsail with Natural UV protection
- Dacron self-tacking jib with Natural UV protection

MOORING LINES - MOORING

- Polyester bowsprit with integrated anchoring gear and bobstay with spinnaker chainplate (for Code 0 and asymmetric spinnaker)
- · Self-draining chain locker, Clench bolt, Piston-driven cover
- · Single roller stainless steel bow fitting
- 12 V 1 500 W vertical electrical windlass Remote control in mooring locker
- 6 Aluminium mooring cleats (Length: 40 cm / 1'4")
- · Stainless steel chafing plate

SAIL LOCKER

Access through T70 deck hatch, Passage width: 0,65 x 0,65m / 2'2" x 2'2"

- Stainless steel ladder
- · Shelving and stowage trays
- LED lighting
- 1 230V socket

SAFETY ON DECK

- · 1 Stainless steel open pulpit
- · 2 Stainless steel aft pulpits with integrated fairlead
- 1 Stainless steel aft central pulpit (Height: 960mm / 3'2")
- 4 Stainless steel handrails on coachroof (2 Genoa track)
- · 1 Lifebuoy support bracket on aft pulpit
- Wooden flagstaff (1 m/3'3") with integrated support on deck
- Double guard lines and stainless steel stanchions (Height: 620mm / 2') - Side boarding gate on either side
- · Emergency ladder on pushpit

COCKPIT

- · Self-draining cockpit
- Teck decking
- · 2 Sail lockers below cockpit seating
- 2 Stowage lockers behind the cockpit with stainless steel support for the fenders (650 x 390mm / 2'2" x 1'3")
- 1 Access hatch to tender garage
- 2 Cockpit tables on stainless steel fixed base, teak table top with 2 extension leaves, stainless steel cup holders on the ends with handrail function and 1 long handrail along its full length (electric base in trim)
- · Natural solid wood slatted cockpit benches
- · 2 Aft helmsman's seat with stowage, teak slats
- · Side helm's seats, slatted teak
- · Foldaway helmsman foot chock
- · 2 Steering wheel consoles:
 - Stainless steel steering wheels with anthracite leather covering (diameter 900 mm/2'11") fixed on white, aluminium lacquered pedestral
 - Steering gear at the helm station
 - Stainless steel steering chain transmission system
- Black lacquered stainless steel hand rail
- 1 Emergency tiller
- 1 Steering compass on port console
- Engine throttle and control panel on starboard
- 1 PPMA folding companionway door in the bottom of the cockpit -Sliding hatch made of PMMA
- Liferaft locker in front of the companionway (Space for 12 place liferaft: 0,96m x 0,59m x 0,40m / 3'2" x 1'11" x 1'4")
- Courtesy lighting (7 LED lighting points, warm white lighting)
- 2 Waterproof exterior speakers

SWIM PLATFORM / AFT TRANSOM

- Fully opening transom, convertible to bathing platform (2,61m x 0,93m / 8'7" x 3'1")
- 3 Folding access steps to the cockpit to starboard
- Electrically controlled opening on console
- · Natural solid wood decking on swim platform
- 1 Stainless steel, removable bathing ladder with dedicated stowage in the cockpit

TENDER GARAGE

Accessible from the platform and from the cockpit Can be used to house a Highfield UL240 type tender (2,48m x 1,69m x 0,80m / 8'2" x 5'7" x 2'7")

- 1 Touch-operated ceiling LEDs
- · Tender launching system, avaliable as an option
- 1 Cockpit shower with mixer tap in the tender garage



Provisional Specifications - Europe

INTERIOR

- · Alpi walnut woodwork and white lacquered wood (Partitions)
- · Alpikord oak floorings
- · Lounge Falcon Greige 160 fabric internal upholstery
- Mattresses in the cabins (HR foam 35 kg/m³, thickness 120 mm/5")
- Beige padded ceilings and Apli walnut in the central part of the saloon

Standard version: 3 cabins + 2 heads



COMPANIONWAY

Headroom: 2,00m / 6'7"

- Saloon companionway with 5 hanging steps in Alpikord oak, with non-slip coating, LED lighting below each step
- 2 Valencia Meteor encased stainless steel handrails

SALOON

Headroom: 2,00 - 1,97m / 6'7" - 6'6"

Starboard saloon:

- · Long U-shaped bench seat:
 - seats made from HR40 foam
 - soft seating thanks to the memory material trim + padding
- · Saloon table, wooden top, 2 fixed aluminium legs
- Storage under bench seats
- 1 Electrical panel to starboard incorporated into a piece of furniture for access to electrical connections
- · 2 Portholes with integrated blind
- 2 Coachroof windows with pleated blinds including opening porthole with mosquito net
- · 2 Opening deck hatches with mosquito screen/blinds
- Indirect LED lighting below the bench seat and the upper part of the portholes
- · 1 Adjustable reading light
- · 1 USB port dual port
- 1 230V socket
- Audio:
 - Fusion RA70N entertainment system
 - 2 Interior loudspeakers

Port side chart table:

- · Table with storage- moulded wood fiddle Laminated covering
- Long bench seat with back, chaisse-longue function and seat with reclining part to match the list - Seat made from H35 foam + memory material + 2 trim padding
- · 2 Portholes with integrated blind
- · Storage under bench seats
- 1 Storage space along the hull + 1 Valet tray
- · Indirect LED lighting on the upper part of the portholes
- 1 Adjustable reading light
- 1 230V socket, close to forward bulkhead
- · 1 USB port dual port
- · Pillar with beige cover

GALLEY - PORT

Headroom: 2,01m / 6'7"

- · C-shaped galley
- · Corian Glacier White work surface with Apli walnut moulded rails
- 1 1 rectangular stainless steel sink 1 Mixer tap with hot/cold water under pressure
- 1 Gas cooker 3 burners Stainless steel grill and oven swivels (17L)
 Stainless steel protection handrail Stowage below the oven with drop-down door
- 1 Stowage on work top with top opening (Space for optional 36 L stainless steel cool box, included in the Luxe trim level)
- 12 V 174 L fridge with integrated 16 L freezer (-18 °C), 1 Front opening door
- · Fitted lockers and closed shelving
- 1 Bin (20L)
- · 1 Base unit: 1 drawer on the side, 2 doors, 1 shelf
- Coachroof window with pleated blinds, including 2 opening portholes with mosquito net

OWNER'S CABIN

Headroom: 2,01 - 1,96m / 6'7" - 6'5"

- Central double bed (2,00m x 1,60m 1,15m / 6'9" x 5'3" 3'9") with Lounge Greige 160 fabric padded bedstead
- 1 Bed access sideboard
- 1 Chair on each side of bed with Lounge Greige 160 fabric
- · 2 Shoe stowage beneath the bed
- 2 Hanger closets, with incorporated LED lighting
- 1 Central full-height unit with LED lighting: 4 drawers at the bottom,
 1 door with 4 shelves, mirror inside the door
- 2 Night tables
- 2 Flexible and adjustable bedside lamps
- 1 T60 flush deck hatch with blind/mosquito net
- · 2 Portholes with rigid sliding blind
- 1 230 V power socket on each side of the bed
- 1 dual port USB outlet on each side of the bed
- · LED indirect lighting + Spot lighting

2 PRIVATE HEADS

To starboard:

Headroom: 1,92m / 6'4"

- 1 Manual toilet
- 1 80 L / 13 US Gal rigid holding tank
- Work top in Corian Glacier White
- · 1 Integrated polyester basin Mixer tap
- 1 Cabinet Mirror
- · Toilet accessories
- · 1 Deck hatch with mosquito screen/blind
- · LED indirect lighting + Spot lighting

to port:

Headroom: 1,97m / 6'6"

- · Shower with seat and wooden shower base
- · 2 Open stowage trays
- 1 Deck hatch with mosquito screen/blind
- LED indirect lighting



Provisional Specifications - Europe

PORT AFT CABIN

Headroom: 1,92m / 6'4"

- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- 1 Hanging locker, 1 Cupboard with shelves, with incorporated LED lighting
- · 2 Lockers with top opening along the hull
- · 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- 1 Flexible and adjustable reading light on the hanging locker
- 1 USB port dual port
- 1 230V socket
- · 1 Porthole with rigid sliding blind
- · 1 Opening window with below cockpit seat with pleated blind
- 2 Opening windows on coaming with pleated blind (1 with the 3 heads version)

STARBOARD AFT CABIN

Headroom: 1,92m / 6'4"

- 1 Double bed (2,04m x 1,40m / 6'8" x 4'7")
- · 1 Hanging locker, 2 lockers with top opening along the hull
- 1 Bed access sideboard
- 1 Drawer under the bed
- 1 Large stowage under the bed, top opening (location for air conditioning option)
- 1 Flexible, swivelling reading light at bedhead
- · 1 Flexible and adjustable reading light on the hanging locker
- · 1 USB socket
- 1 230V socket
- · 1 Porthole with rigid sliding blind
- · 2 Opening windows with below cockpit seat with pleated blind
- · 1 Opening window on coaming with pleated blind

AFT STARBOARD HEAD COMPARTMENT

Headroom: 1,95m / 6'5"

Access from the saloon or the starboard aft cabin

- Separate shower 1 Mixer tap White polyester shower base
- · Corian Glacier White work top with self-draining storage
- · 1 Manual toilet
- 1 80 L / 21 US Gal rigid holding tank
- 1 Washbasin 1 Mixer tap
- 1 Cabinet + Storage space under the basin
- 2 Mirrors
- Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen

3 cabins 3 heads version (Option)



This head stands between the galley and the after port cabin: single hanging locker and one opening porthole in the aft cabin

AFT PORT HEAD COMPARTMENT

Headroom: 2.03m / 6'8"

Access by the aft starboard cabin

- Polyester work top with integrated basin 1 Mixer tap 1 Shower -White polyester shower base
- 1 Manual toilet
- 1 50 L / 13 US Gal rigid holding tank
- 1 Bathroom cabinet 2 doors
- 1 Mirror above the washbasin
- · Toilet accessories
- 1 Opening porthole on coaming in side window, opaque film, mosquito screen
- · 1 Fixed window on coaming, opaque film



Provisional Specifications - Europe

ENGINE

- · Engine Yanmar Diesel:
- 80 HP/80 HP, Sail Drive, Common Rail (standard)
- 80 HP/80 HP, Sail Drive, Common Rail Dock & Go (Option)
- 110 HP/110 HP, Propeller shaft, Common Rail (Option)
- Engine control at the starboard helm station Control panel
- Engine compartment:
 - Soundproofing foam
 - Ventilation: 2 air intakes and 1 forced air outlets
 - Automatic LED lighting
- · Engine data visible on the B&G screen
- 1 Alternator (12V / 125 Ah)
- 2 Rotomoulded diesel tank 2 x 200 L/2 x 53 US Gal (under aft berth port and starboard) - Electronic gauge - Low level alarm - 1 Deck filler
- · Filters: Seawater Diesel Water separator
- · Foldaway three-blade propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Engine access through aft cabins

PLUMBING ___

- 1 Rotomoulded freshwater tank 380 L / 100 US Gal, under berth in forward cabin - 1 Deck filler
- 2 Rotomoulded freshwater tanks 2 x 150L / 2 x 40 US Gal, under saloon floor, port and starboard - 1 Deck filler
- · Pressurised electric water pump Expansion tank Inline filter
- 40 L / 11 US Gal Electric water heater (engine use)
- 1 Rigid black water holding tank for each WC
- · Electrical shower drain pumps
- 1 Electric bilge pump
- 1 Manual bilge pump
- Transfer valves easily accessible from the companionway

GAS

- 1 Box for 2 gas bottles in the anchor locker (Diameter: 0,28m / 11"x Height: 0,45m / 1'6")
- · Regulator and safety tap
- · Gas leak detector

ELECTRICITY

- 12 V electrical panel (Breaker, Voltmeter, Water gauge, Fuel gauge, Battery warning, Fuel warning, Water warning) + USB port dual port + Navicolor 3.5" screen
- Radio controlled wireless light switches (no battery) for lighting (excluding heads)
- Ship Control technology control numerous functions from the navigation screens (or from a tablet or smartphone using a dedicated app):
- Anchoring and masthead navigation lights
- Lighting of boom, spreaders (optional), underwater spotlights (optional)
- Courtesy light in cockpit
- Direct lighting
- Deck searchlight
- Inverter (Option)
- Fridge
- Water unit
- Bilge pumps
- Air conditioning (Option)
- Generator (Option)
- Audio
- Monitoring of tanks
- Battery monitoring
- 12V circuit
- 3 AGM service batteries (140 Ah)
- 1 AGM engine battery (100 Ah)
- · Battery cut-off switch easily accessible from the companionway
- 1 Battery charger (60 Ah)
- 1 Power distributor
- · 10 230V Sockets:
 - 2 in the forward cabin
 - 1 in the forward port head
 - 1 in the aft cabins
 - 1 in the saloon (Starboard)
 - 1 at chart table
 - 1 in galley
 - 1 in the engine compartment
 - 1 in the sail locker
- 6 Dual USB socket:
 - 2 in the forward cabin
 - 1 in the aft cabins
 - 1 on the electrical panel
 - 1 at chart table
- 1 Shore power socket 230 V, next to the helm station
- · LED lighting:
- Overhead lights, with dimmer
- Reading lights
- Indirect lighting, with dimmer
- LED navigation lights:
 - 1 Masthead light
 - 1 Steaming light
 - 1 Anchor light on masthead
- Deck searchlight (Halogen)
- · Wire runs for option cables



Provisional Specifications - Europe

TRIM LEVEL & PACKS

TRIM LEVEL _____

	CONFORT	LUXE
Coastal B&G Pack		
1 Port electric Harken H50.2 STAEH rigging winch (in lieu of standard)	-	_
Windlass control in cockpit with chain counter	-	
Tilting transom remote control	_	_
• Tunnel bow thruster + 4 Dedicated batteries (50 Amps - 12V) + 1 Battery charger (30 Amps - 24V)	_	
TECMA electric fresh water/sea water WC in the owner's head	_	
IBS sensor	_	
2 Additional 140 ampères service batteries		
Additional 40 ampères battery charger		
Electrical engine control on the starboard console	•	
Mosquito nets for opening portholes		
Spring mattress in the owner's cabin (thickness: 180mm / 7")	•	
Offshore B&G Pack		
2 Electrical bases for the cockpit tables for use as sundeck		
Cockpit table covers, Charcoal Grey		_
Diamante Snow exterior cockpit upholstery:		_
- seats and backs on the cockpit benches: Filter foam 80 mm/3" thickness (Density: 60F + 20S)		_
- Helm seats: stainless steel backrest and upholstery on back		
- 2 Companionway sundecks with reclinable backs (ratchet system)		
- 2 Cushions for the cockpit tables for use as sun deck		
Quiet Flush fresh water/seawater electric WC in the aft starboard head		
36 L cool box with access from the galley work top, stainless steel tank (temperature adjustable from		
+10 °C to -12 °C)		•

ELECTRONICS PACKS: B&G _____

	COASTAL (included in the Confort trim level)	OFFSHORE (included in the Luxe trim level)
 Port and starboard helm stations: 1 12" Zeus³ wide wireless multi-function touchscreen (GPS, Chart plotter, Card reader - Navionics Silver cartography included) 		•
Windvane, Anenometer B&G	•	
Sensor (Log, Speedometer, Temperature)	•	•
 PC interface V90S VHF radio fixed to the chart table, AIS receiver function 	•	•
Windex Windvane	-	
Protective covers for helm & consoles (Charcoal Grey)		-
Pilot B&G NAC3		
WR10 Wireless autopilot remote control		•
H50 wireless VHF set		•



Provisional Specifications - Europe

RIGGING PACKS (Compatible with the 2 masts)

	DOWNWIND	UPWIND	DOWNWIND + UPWIND
German System (Two-way mainsheet at the helm station + 2 additional clutches to starboard and 2 to port)	•	•	•
• 2 Genoa winches (H60.2STA) + 1 Winch handle		•	•
Asymmetrical spinnaker rigging / Code 0			•
Dacron genoa on furler		•	•
Genoa sheet track on the coachroof + Genoa sheets		•	•

STAYSAIL RIGGING PACK (Compatible with the 2 masts)

- · 1 Clutch to starboard
- · 1 Wichard double chainplate on forward deck for removable forestay
- 1 Dyneema halyard sheave with block for staysail

HARKEN AST PACK (for mast with in-mast furling or classical mast, incompatible with the rigging packs)

- 1 Rewind Harken H46.2 STAEH AST electric winch 12V
- 2 Rewind Harken H60.2 STAEH AST electric Genoa winch 12V
- System Harken AST 1 dedicated screen on the port console which can be used to activate 3 full functions for navigation until complete control:
 - Automatic sail adjustment
 - Assisted tacking changes
 - List limiter
- · Emergency stop system on the port console + audible alarm
- Asymmetrical spinnaker rigging/Code 0
- · Genoa sheet track on the coachroof + Genoa sheets
- Dacron genoa on furler

MOORING PACK

- Delta 32 kg/71 lbs anchor (galvanized steel) (stainless steel anchor upgrade as an option) Chain (Diameter: $12 \text{mm} / \frac{1}{2}$ " Length: 85 m / 279°) Line (Diameter: $22 \text{mm} / \frac{7}{8}$ " Length: 4 m / 13")

- · 6 Fenders:
- 4 XL (Diameter: 300mm / 12" Length: 880mm / 2'11")
- 2 L (Diameter: 250mm / 10" Length: 700mm / 2'4")
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3')

MOORING PACK (inflatable)

- Delta 32 kg/71 lbs anchor (galvanized steel)
 Chain (Diameter: 12mm / ¹/₂" Length: 85m / 279')
 Line (Diameter: 22mm / ⁷/₈" Length: 4m / 13'1'')
 6 Fenders (Diameter: 360mm / 1'2" Length: 1 200mm / 3'11'')
 4 Moorings lines (Diameter: 18mm / ¹¹/₁₆" Length: 15m / 49'3'')



Provisional Specifications - Europe

OPTIONS

NAVIGATION ELECTRONICS: B&G _

- 4G Radar (Halo 20+)
- Chart table: 12" Zeus wide wireless multi-function touchscreen
- Forward Scan Sensor (Forward underwater vision)
- AIS NAIS 500

RIGGING - SAILS

- · FurlerBoom V-shaped boom furler, grey lacquer
- · Aluminium canoe boom, Sparcraft grey lacquer
- · Hydranet mainsail
- · Hydranet self-tacking jib (in place of the Dacron, standard)
- Genoa Hydranet (implies rigging pack)
- Code 0 with "Top Down" furling system
- · Electric Genoa furler on deck

WINCHES _

- 2 Electric Harken genoa sheet winches (H60.2 STAEH)
- 1 Harken starboard manoeuvre electric winch (H50.2 STAEH)

HULL - DECK - COCKPIT

- · Pearl grey gel-coat (Hull & Bowsprit)
- Blue grey gel-coat (Hull & Bowsprit)
- Metallic hull paint (Hull Aft transom Gunwale Bowsprit) Solid wood slatted side decks option required
- Retractable capstan (Bow)
- Coachroof sprayhood, Lexan rigid glazing, Charcoal Grey
- Cockpit bimini with LED lighting, Charcoal Grey
- Side sunshades for the cockpit bimini (Batyline)
- · Cockpit bimini full enclosure (2 sides + aft), Charcoal Grey
- Diamante Snow sundeck for the forward deck, built-in cup holders (requires Luxe trim level)
- Dolce 51 cockpit upholstery replacing the Diamante Snow upholstery in the Luxe trim level
- Dolce 51 sundeck for the forward deck, built-in cup holders (requires Luxe trim level)
- · Gas grill on the aft pulpit, removable
- · LED lighting of spreaders
- Sunshade on foredeck, Charcoal Grey
- Retractable stern thruster
- Black or white composite steering wheels
- Stainless steel upgrade to replace the galvanized anchor in the mooring packs
- NOMEN galvanized aluminium retractable cleats (in lieu of standard)
- Accommodation ladder
- Outboard engine bracket, on the aft pulpit
- Polyester folding gangway (2,6m / 8'6")
- · Electric inflator/deflator for tender and fenders (portable, batterypowered)
- Shore fresh water supply
- Cockpit shower, additional (hot/cold water)
- · Tender launching system (folding ramp with roller for recovering the aft platform, 1 manual winch)
- Seawater/fresh water deck washing pump
- 3 Underwater lights (1 forward, 2 aft)
- Composite flagstaff 1,20 m/3'11" (in lieu of standard)

DOCK & GO VERSION

- Engine: YANMAR Common Rail Diesel
- · Swiveling Sail Drive base
- Joystick
- Vessel Management Unit (VMU)
- · Bow thruster
- Autopilot



INTERIOR EQUIPMENT

LAYOUT VERSIONS

- · 3 cabins 2 heads version
- · 3 cabins 3 heads version
- Skipper cabin replacing the sail locker of the foredeck: Access through T70 deck hatch, Stainless steel ladder, 1 Berth, Toilet, Washbasin, Shower, 1 USB port dual port

AMBIANCE

- Interior woodwork: Alpi oak 3 gloss + Alpikord oak floorings
- Internal upholstery according to colour chart: Fabrics, Leather, Nubuck, Ultraleather

MULTIMEDIA

- TV pre-assembly on lifting system, in the saloon
- TV pre-assembly, in the forward cabin (on bulkhead)
- Hifi APOLLO + Bose 2.1 speakers, in the saloon (in lieu of standard)

DOMESTIC APPLIANCES

- · Dishwasher for 6 sets
- · Built-in 22 L grill and microwave combined oven
- Wine cellar 23 bottles
- · 3 kg washer dryer

ON BOARD COMFORT EQUIPMENT

- · Spring mattress in the aft cabins (thickness: 160mm / 6")
- Double berth in saloon (Electric table pedestal + cushion)
- Generator (7,5 KVA, 230V, 50Hz)
- Watermaker (60 l/h / 16 US Gal/h)
- · Air conditioning 44 000 BTU
 - (+ Shore socket extension cord 15m / 49'3") 32A
- Forced air heating fuel
- · Safe, in the forward cabin
- 12V / 230V inverter 2 000 VA
- · Electric battery switch (connected to the Ship Control, controls powering on or shut-off of batteries remotely)
- Lithium battery replacing the AGM batteries Weight saving: Approximately 170 kg / 375 lbs (requires Confort trim level)
- Seawater electric pump, in galley